



Visit product page



FOS IQ PAR IP65 LIME

L006721

IP65



Contemporary IP65 led par with Wireless DMX operation and amazing color mixing, 19 LEDs 12 watts RGB + LIME , 26 degrees beam angle, 0-100% linear dimmer, flicker-free, 3 pixels rings, strobe effect with 1-25T /s, 22/10 DMX channel, IP rated power and DMX connector IN/OUT, Dual mounting brackets for installation/floor stand, Built, noise-free aluminum cooling system, built-in programs, and macro effects. 4.7 kg

TECHNICAL DETAILS

Light source / Optics

Based on 19 x 12 Watt RGB Lime LEDs.
50,000 hours approximate lifespan.
26 degrees beam angle.
Flicker-free operation, suitable for TV applications.

Effects

Red, Green, Blue, & Lime color mixing.
Preset colors/chases and color temperature adjustment DMX channel.
3 controllable independent ring LED sections (center, middle & outer).
Linear dimming & strobe.

Control

DMX / Auto & Sound operation.
Integrated wireless receiver, compatible with the AirLink series.
DMX control with 22 or 10 channels.

Technical Specifications

Power Supply: AC90 / 260 Volt, 50/60 Hz.

Power Consumption: 200 Watt.

IP65, suitable for outdoor use as well.

IP rated 3pin XLR & Truepowercon connectors.

Net Weight: 4,65 Kg

Gross Weight: 5,65 Kg

Dimensions: 155 x 299 x 279 mm (D x W x H).

Packing Dimensions: 370 x 335 x 245 mm (D x W x H).

Wireless Indicator Index

Wireless connection with the AirLink transmitters can be done in a simple way. The different colors and states will help you understand the status of the connection:

White: The fixture has been not paired with any transmitter yet. It is ready for pairing.

Red (flashing): The connection with the transmitter is lost.

Green (fast flashing): Connecting/pairing with the transmitter.

Green (slow flashing): Connected, with no DMX signal.

Green (steady on): Connected, with DMX signal.

Packing Details

Carton box for 1 pc: 37 x 33 x 24 cm - 5.5 kg

Carton box for 4 pcs: 70 x 50 x 40 cm - 23 kg

PHOTOS



PRODUCT VIDEO



ACCESSORIES



FOS AirLink Foldable

AirLink DMX transmitter for the Solo / Luminus / N



FOS AirLink PRO

AirLink DMX transmitter for the Solo and Luminus P



FOS Case IQ Par IP65

Flight case with wheels for 8pcs IQ Par IP65.



FOS CLAMP 100

Professional clamp for fixtures lifting weight 100



FC-TP-PDC-1.5

Professional TruePowercon/ DMX cable 1.5 meter.



FOS AirLink 24

AirLink DMX transmitter/ fader desk for the Solo a

