



Visit product page



## FOS PAR 18X10WPRO IP65

L004961

Weatherproof aluminium led par with IP connectors , Beam aperture: 30°, 18 RGBW 10w LEDs (4in1)Dimmer: 0-100% stop/strobe effect, aluminium 4kg, noiseless cooling system.

### TECHNICAL DETAILS

#### Light Source/Optics

18 RGBW 10w LEDs (4in1)  
Average lifespan: 50000 Hours  
Beam aperture: 30°  
Noiseless cooling system

#### Effects

RGBW dimming/fade.  
RGBW color mixing  
Auto programs with speed adjustment  
Preset colors  
Dimmer: 0-100% linear dimming  
Adjustable speed stop/strobe effect (1-10 flash/sec)

#### Control

Control modes: DMX 512 (4 / 8 DMX channels), sound activated, auto mode  
Stand-alone mode and Master/Slave modes  
Data in/out: 3 pin XLR IP65

## Installation/Dimension Details

Voltage: 90 to 240 Volts – 50/60Hz

Power consumption: 200 Watt

IP65 cables input and output

Double yoke system, which act as a floor stand

Operating positions: all (device on floor or fixed to a support). IP65 protection from dust and water, suitable for outdoor applications.

Maximum permitted ambient temperature (Ta max): 45°C (113°F). Minimum permitted ambient temperature authorized (Ta min): -10°C (14°F).

Dimensions: Par diameter 22 cm, depth 12 cm, height (with yoke in vertical position 26 cm).

Weight: 4,6 Kg.

## PHOTOS



## PRODUCT VIDEO



## ACCESSORIES



### FOS Case 8in1 PAR PRO

Flight case with wheels for  
8pcs Pro series and T

### FOS SUPER CLAMP 200 BLACK

Professional clamp for  
fixtures lifting weight 200

### FOS SUPER CLAMP 200

Professional clamp for  
fixtures lifting weight 200

