



Visit product page



FOS TOURING PAR 7X15 IP HEX

L005528

Weatherproof aluminium led par with IP True powercon connectors , Beam aperture: 25°, 7 RGBW+Amber+UV 15w LEDs (6 in1)Dimmer: 0-100% stop/strobe effect, aluminium 3kg, noiseless cooling system.

TECHNICAL DETAILS

Light Source / Optics

Light source: 7x 15 Watt RGBWAUV 6 in 1 LEDs.
Beam angle: 25°.

Effects

RGBWAUV color mixing.
Dimmer from 0 to 100%.
Strobe effect with variable speed.
Color macros and effects.

Control

Manual (on-board control), sound mode, auto, sound and DMX.
DMX control with 6 or 10 channels.

Installation / Dimension details

Power supply: 100/240 Volt AC, 50/60 Hz.
Power consumption: 105 Watt.
Protection rate against dust and water: IP65
Net weight: 3,1 Kg.
Dimensions (projector only): 165 mm length x 173 mm width x 150 mm height.

Dimensions (with the yoke and projector in vertical position): 215 mm length x 150 mm width x 240 mm height.

Packing Details

Carton box for 8 pcs: 46 x 47 x 57 - 30 kg

PHOTOS



PRODUCT VIDEO



ACCESSORIES



FC-PT

Powercon true male/female set.



FC-TP-PDC-3

Professional TruePowercon/ DMX cable fixture lifting weight 200 3 meter.



FOS SUPER CLAMP 200

Professional clamp for fixtures lifting weight 200



FOS SUPER CLAMP 200

BLACK

Professional clamp for fixtures lifting weight 200

