



Visit product page



## FOS TORNADO PRO

L006160

Innovative multi-use IP65 for outdoor and indoor applications strobe, total 24 pixels full controllable, 8 blinding pixels by 96 leds cool white 5 watt and 16 color paint pixels by 672 leds 0.3 watt RGB SMD, Beam angle: 120°, DMX channels: 12/59ch, weatherproof IP65 XLR and PowerCON Seetronic connectors, OLED display, 9.5 kg

### TECHNICAL DETAILS

#### Fixture Description

Innovative multi-use IP65 for outdoor and indoor applications strobe, total 24 pixels full controllable. Static strobe effect, with pixel RGB (x16 zones) and White (x8 sections)!  
IP65: Suitable for outdoor use as well, in events / stages / temporary installations.

#### Light Source / Optics

RGB SMD LEDs 672x 0,3 Watt.  
Cool White LEDs, 96x 5 Watt.  
Beam angle: 120°  
Approximate LED lifespan: 50,000 hours.

#### Control

DMX, Auto, Manual, Master / Slave control modes.  
DMX control with 12 or 59 Channels.  
Full pixel section control with 59 channels, 8 sections of white and 16 sections of RGB LEDs, with independent shutter channels.

#### Technical Specifications

Power Supply: 100/240 Volt AC, 50/60 Hz.  
Power Consumption: 400 Watt max.  
Signal Connectors: SeeTronic 3 pin input and output XLR IP65.

Power Connectors: See Tronic PowerCon input and output IP65.

IP65, suitable for indoor and outdoor use.

Dimensions: 546 x 257 x 132 mm.

## Packing Details

Carton box for 1 pc: 57 x 33 x 24 cm - 12 kg

Carton box for 2 pcs: 59 x 35 x 52 cm - 24 kg

## PHOTOS



## PRODUCT VIDEO



## ACCESSORIES



### FOS Case Tornado Pro

Flight case with wheels for  
4 pcs Tornado Pro and

---

